

STARMED MUS UNDERCABINET LED

MUS2/MUS4

SPECIFICATION FEATURES

- HOUSING:** 20 gauge formed cold rolled steel housing with continuous seam welds and ground smooth. Aluminum option available.
- LENS:** Lens is .125 Prismatic Acrylic.
- LED:** Available in three color temperatures 3000°K, 3500°K and 4000°K. Other color temperatures available, consult factory. Standard 0-10V driver provided. Optional dimming function (DM) with 10-100% range.
- FINISH:** White antimicrobial powder coat finish following iron phosphate pre-treatment.
- MOUNTING:** Keyhole slots for easy installation. Mounting screws are not provided.



APPLICATION:

Patient Rooms, Nurse Stations, Desk Stations, Offices, Research Facilities, Laboratories, Display cases, and more.



LABEL:

Fixture is certified to UL standards by Intertek Testing Laboratories.



ORDERING INFORMATION

Ex: MUS2-HC-L1-35-A-UN




KEY

FZ = Fuse*
RW = Row Mounting (consult factory for options)
RS = Rocker Switch (120V standard).
Additional voltage options, consult factory.

CO = Convenience Outlet (120V only)
OC = Motion Sensor (Integral)Δ
DM = 0-10V dimming with 10-100% range.
Dimming wires will be extended outside of fixture.

** Subject to change
* Cannot use with UN voltage
Δ Not available in 347V



	A	B	C
MUS2	1.16"	5.00"	22.50"
MUS4	1.16"	5.00"	46.12"

Notes:
Specifications and Dimensions are subject to change without notice.
For additional options and dimensional details please consult your New Star Lighting Representative.