

## IMPORTANT SAFE GUARDS:

- THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.
- DISCONNECT POWER BEFORE BEGINNING INSTALLATION.
- FIXTURE MUST BE INSTALLED IN COMPLIANCE WITH THE NATIONAL ELECTRIC CODE AND ANY LOCAL CODES.
- TO BE INSTALLED ONLY BY A QUALIFIED ELECTRICIAN.
- PROPER GROUNDING IS REQUIRED TO INSURE PERSONAL SAFETY.
- READ ALL FIXTURE MARKINGS AND LABELS TO ENSURE CORRECT INSTALLATION OF FIXTURE.
- RISK OF FIRE, USE A MINIMUM OF 90C SUPPLY CONNECTORS.
- MAXIMUM MOUNTING HEIGHT OF 8FT. WHEN AN EMERGENCY PACK IS PROVIDED

## INSTALLATION INSTRUCTIONS:

1. PLACE VKI IMAGE ON TOP OF GRID. ROTATE AS NEEDED.
2. PLACE CEILING ADAPTER ON TOP OF VKI IMAGE. TABS ON CEILING ADAPTER SHOULD BE ON TOP.
3. PLACE LIGHT TILE ON TOP OF CEILING ADAPTER.
4. BEND TABS ON CEILING ADAPTER TO SECURE LIGHT TILE TO ADAPTER.

OPTIONAL: HOLES ON TABS CAN BE USED FOR ADDITIONAL SUPPORT TO BUILDING STRUCTURE, IF REQUIRED.

5. OPEN LED DRIVER HOUSING COVER TO ACCESS MAIN LEADS.
6. DISCONNECT POWER. CONNECT HOT BLACK) AND WHITE (NEUTRAL) WIRES FROM LED DRIVER TO APPROPRIATE BUILDING CONDUCTORS.
7. REINSTALL LED DRIVER HOUSING COVER.

