

PROJECT:	
TYPE:	
PRODUCT:	
APPROVED BY	:

HNL STEP LIGHT SERIES: QUICK SHIP

FEATURES:

- Intended for Healthcare Settings, Patient Rooms, Surgical Suites, Commercial Settings, Lobbies, Schools, and more
- 5 Day Quick Ship for orders under 50 fixtures. Consult factory for large quantities or additional fixture options
- Three faceplate options: horizontal or vertical hood, and open frame
- Manufactured in durable die cast aluminum
- Available in 3000°K, 4000°K, 5000°K and Amber

RELATED PRODUCTS:

- HNL Step Light Full Range of Ordering Options
- StarStep SNL3



HNLHH



SPECIFICATIONS

CONSTRUCTION: Durable die cast aluminum material. Available with three different faceplates: Horizontal Hood, Open Frame (can be installed vertically or horizontally), and Vertical Hood.

LED: Available in three white color temperatures 3000°K, 4000°K and 5000°K. Optional amber LED.

ELECTRICAL: Integrated embedded driver (3W). Optional dimming.

FINISH: White antimicrobial finish (standard).

INSTALLATION: Recessed installation. JBox and hardware by others.

WARRANTY: Limited five (5) year warranty.

LABEL: Fixture is certified to UL standards for Wet Location rating (under covered ceiling).

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.



PROJECT:	
TYPE:	

PRODUCT: APPROVED BY:

HNL STEP LIGHT SERIES: QUICK SHIP

ORDERING INFORMATION

EXAMPLE: HNL-HH-30-UN-NF-DM-AM-QS

SERIES	FACEPLATE	COLOR TEMP.	VOLTAGE	OPTIONS
HNL			UN	NF
	HH = Horizontal Hood	30 = 3000°K	UN = Universal	NF = None
	OF = Open Frame*	40 = 4000°K	(120V-277V)	
	VH = Vertical Hood	50 = 5000°K		
		LA = Amber LED		

* Can be installed horizontally or vertically.

DIM	MING	FINISH	
		АМ	QS
ND = None		AM = Antimicrobial White	QS = Quick Ship

DM = 0-10V dimming with 10-100% range

PERFORMANCE DATA*


*Data is with 80 CRI chip. LEDs are frequently updated therefore values may change without notice.

MODEL	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
HNL-OF	3000°K	250	66	3.8
	4000°K	240	63	3.8
	5000°K	253	67	3.8
	Amber LED	170	45	3.8
HNL-VH	3000°K	92	24	3.8
	4000°K	82	22	3.8
	5000°K	95	25	3.8
	Amber LED	61	16	3.8
	3000°K	130	34	3.8
HNL-HH	4000°K	120	32	3.8
	5000°K	133	35	3.8
	Amber LED	88	23	3.8


Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

DIMENSIONAL DATA


HORIZONTAL HOOD



VERTICAL HOOD



OPEN FRAME (VERTICAL OR HORIZONTAL)



Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.