

51H SERIES FLUORESCENT

51HB4

SPECIFICATION FEATURES

HOUSING: 16Ga. cold rolled steel internally reinforced to provide double wall thickness at ends and corners.

LENS: .125" impact resistant clear prismatic UV stabilized polycarbonate diffuser

REFLECTOR: Cold rolled steel, removable and unitized with all electrical components for easy installation and maintenance.

ELECTRONICS: Electronic Ballast <10% THD standard. Lamps by others.

FASTENERS: Six tamper resistant Torx head screws with center pin reject.

FINISH: White powder coat finish following multistage iron phosphate pre-treatment.



APPLICATIONS: High Abuse Areas, Apartment Buildings, School Campuses, Public Housing Complexes, Transportation Terminals, Hotels, Freezer Units, Stairwells, Locker Rooms, Detention Centers, Hospitals, and more.

MOUNTING: Tandem or Pendant style mount available. Hardware and stem by others.

LABEL: Fixture is certified to UL standards.



ORDERING INFORMATION

Example: 51HB4-3281C-D-UN

SERIES	# OF LAMP	LAMP TYPE	CIRCUITS	LENS	VOLTAGE	OPTIONS
51HB4	2 = 2 Lamps	32 = Linear 32W T8	1C = 1 Circuit	B = .125 Prismatic Poly.	12 = 120V	DB = Dimming Ballast (0-10V)*
	3 = 3 Lamps	28 = Linear 28 T5	2C = 2 Circuits	C = .156 Prismatic Poly.	27 = 277V	E1 = Emerg. Ballast (450lm)**
				D = .187 Prismatic Poly.	34 = 347V*	E2 = Emerg. Ballast (1350lm)**
				UN = Universal (120V-277V)	34 = 347V*	FZ1 = Fuse (120V)
						FZ2 = Fuse (277V)
						PR = Program Rapid Start
						SS = Stainless Steel Brushed Housing
						WL = Wet Location (Covered Ceiling Only)
						CW = Cold Weather Ballast (-30°C) T8 Lamp Only
						AH = Allen Head Screws with Center Pin

*Consult factory for lamp-ballast options

* Cannot use with UN voltage.

** Cannot use with UN voltage. Consult factory for T5 availability

51H SERIES FLUORESCENT

51HB4



DIMENSIONAL DATA

Fixture weight varies and is dependent upon chosen specifications.
Average weight of the 51HB4 is ___lbs. Consult factory for additional information.

