

PROJECT:	
ГҮРЕ:	
PRODUCT:	
APPROVED BY:	

51H SERIES FLUORESCENT 51HC2/51HC4

SPECIFICATION FEATURES

HOUSING: 16Ga. cold rolled steel internally reinforced to provide double wall

thickness at ends and corners.

LENS: .125" impact resistant clear prismatic UV stabilized polycarbonate diffuser

REFLECTOR: Cold rolled steel, removable and unitized with all electrical components for easy installation and maintenance.

ELECTRONICS: Electronic Ballast <10% THD standard. Lamps by others.

FASTENERS: Six tamper resistant Torx head screws with center pin reject.

FINISH: White powder coat finish following multistage iron phosphate pre-treatment.



APPLICATIONS: High Abuse Areas, Apartment Buildings, School Campuses, Public Housing Complexes, Transportation Terminals, Hotels, Freezer Units, Stairwells, Locker Rooms, Detention Centers, Hospitals, and more.

MOUNTING: Tandem or Pendant style mount available. Hardware and stem by others.

LABEL: Fixture is certified to UL standards.





ORDERING INFORMATION

Example: 51HC4-2541C-D-UN

SERIES	SIZE	# OF LAMP	LAMP TYPE	CIRCUITS	LENS	VOLTAGE	OPTIONS
51HC		2					
	2 = 2ft	2 = 2 Lamps	51HC2:	1C = 1 Circuit	B = .125 Prismatic Poly.	12 = 120V	DB = Dimming Ballast (0-10V)*
	4 = 4ft		17 = Linear 17W T8	2C = 2 Circuits	C = .156 Prismatic Poly.	27 = 277V	E1 = Emerg. Ballast (450lm)**
			14 = Linear 14W T5		D = .187 Prismatic Poly.	34 = 347V*	E2 = Emerg. Ballast (1350lm)**
	*Nominal Size.		24 = Linear 24W T5 H	10		UN = Universal	FZ1 = Fuse (120V)
	Dimensional		51HC4:			(120V-277V)	FZ2 = Fuse (277V)
	Data on Page 2		32 = Linear 32W T8				PR = Program Rapid Start
			28 = Linear 28W T5			*Consult factory for	SS = Stainless Steel Brushed Housing
			54 = Linear 54W T5 H	10		lamp-ballast options	WL = Wet Location (Covered Ceiling Only)
							CW = Cold Weather Ballast (-30°C) T8 Lamp Only
							AH = Allen Head Screws with Center Pin
							* Cannot use with UN voltage.
							** Cannot use with UN voltage. Consult factory for T5 availability

51H SERIES FLUORESCENT 51HC2/51HC4



DIMENSIONAL DATA

Fixture weight varies and is dependent upon chosen specifications. Consult factory for additional information. Average weight of the 51HC2 is 15lbs. Average weight of the 51HC4 is 35lbs.

