

57S SERIES FLUORESCENT

57S

SPECIFICATION FEATURES

HOUSING: 16Ga. cold rolled steel internally reinforced to provide double wall thickness at ends and corners.

LENS: .125" impact resistant clear prismatic UV stabilized polycarbonate diffuser

REFLECTOR: Cold rolled steel, removable and unitized with all electrical components for easy installation and maintenance.

ELECTRONICS: Electronic Ballast <10% THD standard. Lamps by others.

FASTENERS: Tamper resistant countersunk flat head screws with center pin reject.

FINISH: White powder coat finish following multistage iron phosphate pre-treatment.



APPLICATIONS: High Abuse Areas, Apartment Buildings, School Campuses, Public Housing Complexes, Transportation Terminals, Hotels, Freezer Units, Stairwells, Locker Rooms, Detention Centers, Hospitals, and more.

MOUNTING: Tandem or Pendant style mount available. Hardware and stem by others.

LABEL: Fixture is certified to UL standards for Damp Locations.



ORDERING INFORMATION

Example: 51HC4-2541C-D-UN

SERIES	HOUSING	# OF LAMP	LAMP TYPE	FACE
57S		1		
	B = 14Ga. CRS Painted	1 = 1 Lamp	13E = 13W Twin 2Gx7	OP = Open Face
	C = 16Ga. CRS Painted		13 = 13W Triple Gx24q-1	LD = Louver Door*
	D = 18Ga. CRS Painted		13Q = 13W Quad G24q-1	
	F = 16Ga. SS Brushed		18 = 18W Triple Gx24q-2	*Lens installed inside louver door.
	G = 18Ga. SS Brushed		18Q = 18W Quad G24q-2	
			26 = 26W Triple Gx24q-3	
			26Q = 26W Quad G24q-3	

OUTER LENS	INNER LENS	VOLTAGE	OPTIONS
0 = No Lens	A = .125 Prismatic Acrylic	12 = 120V	DB = Dimming Ballast (0-10V)*
1 = .187 Clear Poly.	B = .125 Prismatic Poly.	27 = 277V	E1 = Emerg. Ballast (450lm)**
2 = .250 Clear Poly.	C = .156 Prismatic Poly.	34 = 347V*	E2 = Emerg. Ballast (1350lm)**
3 = .375 Clear Poly.		UN = Universal	FZ1 = Fuse (120V)
5 = .187 Clear Temp. Glass		(120V-277V)	FZ2 = Fuse (277V)
			PC = Photocell*
		*Consult factory for lamp-ballast options	AH = Allen Head Screws with Center Pin Reject
			AM = White Anti-Microbial Powder Coat Finish

* Cannot use with UN voltage.

** Cannot use with UN voltage. Consult factory for T5 availability.

57S SERIES FLUORESCENT

57S



DIMENSIONAL DATA

Fixture weight varies and is dependent upon chosen specifications. Consult factory for additional information.

