

ALTO HIGH BAY SERIES

ALHB1/ALHB2/ALHB3

FEATURES:

- Intended for Food Zone Non-Contact, Splash Zone and Non-Food Zone Applications, Food Processing Facilities, Natatorium Environments, Manufacturing Facilities, Commercial Kitchens, Gymsnasiums, and more
- Linear high bay available in 1ft, 2ft and 3ft
- Hooks on back of fixture for suspension mounting
- IP69K rating to withstand daily wash-downs
- Sloped design intended for easy cleaning
- Fixture is certified to UL standards. IP69K certified and tested for 1500 PSI. NSF2 Splash Zone/Non-Food Zone/ Food Zone Non-Contact certified.



ALHB3



SPECIFICATIONS

CONSTRUCTION: Non-toxic, strong anti-corrosion aluminum housing with silicone rubber to prevent any contaminations from entering. Aluminum heat sink designed for maximum thermal dissipation. LED modules are sealed and have a clear optic lens for maximum output. NSF-rated Epoxy Polyester powder coat white paint finish.

LED: High-powered LED modules available in 4000°K and 5000°K. Other color temperatures available, consult factory. Minimum 80 CRI standard. Standard beam angle is 90°, consult factory for additional options. Projected life is 50,000 hours at 70% lumen output.

EMERGENCY BATTERY: Optional IP65 external BillDa emergency battery pack. Battery pack is 30W with 90 minutes of emergency time. Includes power box, remote control reception, hook-up, L-shaped bracket, Junction Box, terminal and remote control. Consult factory for more information.

OPERATING TEMP: -40°C to 50°C.

INSTALLATION: Suited for suspension mounting with hooks on back of housing. Power cable located on back of fixture. Optional suspension chain kit available (field installation).

WARRANTY: Limited five (5) year warranty.

LABEL: Fixture is certified to UL standards. IP69K certified and tested for 1500 PSI. NSF2 Splash Zone/Non-Food Zone/Food Zone Non-Contact certified.

