

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 PRODUCT: \_\_\_\_\_  
 APPROVED BY: \_\_\_\_\_



ST

## PRODUCT FEATURES

- Intended for Cleanrooms, Hospitals, Hi-Tech Manufacturing, Laboratory, Food Processing Facilities, Commercial Kitchens and more
- Grid or flange installation
- Fixture is certified to UL Standards by Intertek Testing Laboratory. IP65 Rated per IEC60598. NSF2 Splash/Non-Food Zone listed. Meets ISO4 Cleanroom standards.
- This product is Made in America and complies with the Buy American Act (BAA)

## ORDERING INFORMATION

Example: STF24-HC/OC-L4401C-A-UN



ST					
<b>Series</b>	<b>Mounting</b> G = Grid F = Flange	<b>Nominal Size</b> 22 = 2x2 24 = 2x4  *Nominal size. Dimensional data on Page 2.	<b>Housing</b> HC = 20Ga. CRS Painted HS = 20Ga. SS Brushed HP = 20Ga. SS Painted HA = 16Ga. Alum. Painted	<b>Overlapping Frame</b> OC = 18Ga. CRS Painted OS = 18Ga. SS Brushed OP = 18Ga. SS Painted OA = 16Ga. Alum. Painted	<b>Lumen Output*</b> L2 = Standard L4 = Standard L6 = Medium L8 = High CL = Custom Lumen Output**  *Subject to change. Performance Data on page 3. ** Must be specified at time of quote. Must not exceed fixture maximum output. Must specify "DMI" if selecting dimming.

<b>Color Temp.</b> 35 = 3500K 40 = 4000K 50 = 5000K	<b>Circuits</b> 1C = 1 Circuit 2C = 2 Circuits	<b>Lens</b> A = .125 Prismatic Acrylic B = .125 Prismatic Poly. C = .156 Prismatic Poly. D = .187 Prismatic Poly. E = .125 White Frost Poly. G = .140 Prismatic DR Acrylic	<b>Voltage</b> 12 = 120V 27 = 277V 34 = 347V UN = Universal (120V-277V)	<b>Options</b> FZ1 = Fuse (120V) FZ2 = Fuse (277V) SD2 = Step Dim. Module (50-100%)* SD3 = Step Dim. Module (30-70-100%)* EL1 = Emerg. Batt. LED Low (10W)** EL2 = Emerg. Batt. LED High (20W)** RF = (RIF) Radio Interference Filter TH = Torx® Head screws (with center pin) 90C = 90 CRI  *Consult factory for 347V. **If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity.
--	--	--	---	---



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
 (773) 847-1400  
 www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2024, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

## SPECIFICATIONS

**HOUSING:** 18-Gauge formed cold rolled steel housing with continuous seam welds. Aluminum and stainless steel options available.

**FRAME:** Overlapping doorframe available in aluminum, cold rolled steel, and stainless steel. Frame held to housing via aircraft cable.

**LENS:** Acrylic lens with smooth side out. Alternate lens options available including Prismatic Polycarbonate and a White Frosted Polycarbonate. Overlapping frame uses a rail hold down system.

**LED:** Available in three color temperatures 3500K, 4000K, and 5000K with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 50,000 hours with 70% lumen maintenance in an ambient environment 25°C temperature, compliant with IES LM-80 testing data.

**ELECTRICAL:** 120-277Vac 50/60Hz, constant current driver (<20% THD, >0.9 PF). Standard 0-10V Dimming with 1-100% range.

**FASTENERS:** Stainless steel Philips flat head screws with captive cage nuts. Finish to match housing.

**FINISH:** White antimicrobial powder coat finish following multistage iron phosphate pretreatment.

**GASKET:** Closed cell EPDM and closed cell silicone gaskets prevent air contaminations from entering the fixture.


**MOUNTING:** Grid or Flange installation. Flange fixtures come with adjustable 90° swing arm for easy installation. Mounting for custom ceilings available, consult factory. Mounting for custom ceilings available, consult factory.

**WARRANTY:** Limited five (5) year warranty.


**LABEL:** Fixture is certified to UL Standards by Intertek Testing Laboratory. IP65 Rated per IEC60598. NSF2 Splash/Non-Food Zone listed. Meets ISO4 Cleanroom standards.

### GRID MOUNTING

#### DIMENSIONAL DATA



### FLANGE MOUNTING



	A	B	C	D	REC. CEILING CUT-OUT
<b>STG22</b>	23.69"	6.41"	24.11"	23.69"	-
<b>STG24</b>	23.69"	6.41"	48.12"	23.69"	-
<b>STF22</b>	26.50"	6.75"	25.13"	26.13"	24.375" x 24.375"
<b>STF24</b>	26.50"	6.75"	50.13"	26.13"	24.375" x 48.375"



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
(773) 847-1400  
www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2024, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

## PERFORMANCE DATA

\*Data is with 80 CRI chip. LEDs are frequently updated therefore values may change without notice.

MODEL	OUTPUT	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/w)	INPUT POWER (W)
ST22	Low	3500K	3000	120	25
		4000K	3125	125	25
		5000K	3250	130	25
	Standard	3500K	6000	120	50
		4000K	6250	125	50
		5000K	6500	130	50
	Medium	3500K	8625	115	75
		4000K	9000	120	75
		5000K	9375	125	75
	High	3500K	11500	115	100
		4000K	12000	120	100
		5000K	12500	125	100
ST24	Low	3500K	6000	120	50
		4000K	6250	125	50
		5000K	6500	130	50
	Standard	3500K	12000	120	100
		4000K	12500	125	100
		5000K	13000	130	100
	Medium	3500K	17250	115	150
		4000K	18000	120	150
		5000K	18750	125	150
	High	3500K	23000	115	200
		4000K	24000	120	200
		5000K	25000	125	200



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
 (773) 847-1400  
[www.newstarlighting.com](http://www.newstarlighting.com)

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2024, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.