

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____



CCEX Series

PRODUCT FEATURES

- Intended for Commercial applications such as offices, medical office buildings, corridors, lobbies, waiting rooms, and more
- Canopy for Top or End Mount. Universal knockout on back plate for Wall Mount
- Field-selectable Red, Green or Red/Green legend. Universal Single/Double face
- UL Damp, UL924, NFPA101 Life Safety Code, NEC, OSHA, Certified to CEC under Title 20 Regulations

ORDERING INFORMATION

Example: CCEX-UF-RW-WH-EM



CCEX	UF				
Series	Face UF = Universal Single/Double Face	Lettering RW = Red Letters GW = Green Letters RGW = Red/Green Letters	Housing Color WH = White BK = Black	Battery Blank = AC-Only EM = Emergency Battery	Options CUS = Custom Signage* SDT = Self-Diagnostics** *Consult factory **Available only with EM units. Not available with RG units



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
 (773) 847-1400
 www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

SPECIFICATIONS

CONSTRUCTION: Injection-molded, engineering grade, 5VA flame retardant, high-impact resistant thermoplastic. Aesthetically pleasing, curved face, rounded corner design. Snap-out chevron directional indicators.

ELECTRICAL: Dual 120V/277V standard. Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two-rate charger initiates battery charging to recharge a discharged battery in 24 hours. 1.2V long life, maintenance-free, rechargeable NiCd battery (EM models only).

FASTENERS: Stainless steel Philips fasteners.

INSTALLATION: Canopy for Top or End Mount. Universal knockout on back plate for Wall Mount.

WARRANTY: Limited five (5) year warranty.

LABEL: UL Damp, UL924, NFPA101 Life Safety Code, NEC, OSHA, Certified to CEC under Title 20 Regulations.

DIMENSIONAL DATA

