

CLEANROOM EXIT RECESSED SERIES



PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____

PRODUCT FEATURES

- Intended for Cleanrooms, Hospitals, Hi-Tech Manufacturing, Laboratory, Food Processing Facilities, Commercial Kitchens, and more
- Recessed mount installation
- Red or green legend
- Fixture is certified to UL standards by Intertek Testing Laboratory. IP65 rated per IEC60598. Meets ISO4/Class 1 Cleanroom Standards
- This product was Made in America and complies with the Buy American Act requirements



ESCR Series

ORDERING INFORMATION

Example: ESCR-HC/IC-SF-LED-UN-RW



ESC	R			SF		LED
Series	Mounting R = Recessed	Housing HC = 20Ga. CRS Painted HS = 20Ga. Stainless Steel	Overlap Frame OC = 20Ga. CRS Painted OS = 20Ga. SS Brushed	Face SF = Single Face	Panel Options EXIT 1 = No Arrow EXIT 2 = Double Arrow EXIT 3 = Right Arrow EXIT 4 = Left Arrow STAIRS 1 = No Arrow STAIRS 2 = Double Arrow STAIRS 3 = Right Arrow STAIRS 4 = Left Arrow	Lamp Type LED = LED Module

Voltage 12 = 120V 27 = 277V UN = Universal (120V-277V)	Lettering RW = Red Letters GW = Green Letters	Options EM = Emergency Battery *If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity.
--	--	--

SPECIFICATIONS

CONSTRUCTION: 20-Gauge formed cold rolled steel or brushed stainless steel housing with continuous seam welds.

FRAME: Single face overlapping doorframe in 18-gauge cold rolled steel or 18-gauge brushed stainless steel.

LENS: .125 clear polycarbonate lens.

ELECTRICAL: Long life LED system illuminates Red or Green legend. Optional single face or double face. 7W. Must connect power source to an emergency system for 90 minutes of illumination during power loss.

LEGEND: Legend illuminated by internal high output LEDs. Lettering 6" high with .750" stroke. Polycarbonate red or green letters against white translucent background panel. Field selectable chevron inserts.

FINISH: White antimicrobial powder coat finish following multi-stage iron phosphate pre-treatment. Stainless steel housing and overlapping frame will be left unpainted if specified.

GASKET: Closed cell EPDM and closed cell silicone gaskets prevent air contaminations from entering the fixture.

INSTALLATION: Recessed installation.

WARRANTY: 5 Year Warranty.

FASTENERS: Stainless steel Phillips flat head fasteners with captive cage nuts. Finish to match doorframe.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory. IP65 rated per IEC60598. Meets ISO4/Class 1 Cleanroom Standards. This product is Made in America and complies with the Buy American Act (BAA).

DIMENSIONAL DATA

