CLEANROOM EXIT RECESSED SERIES



PROJECT:
TYPE:
PRODUCT:
APPROVED BY:

PRODUCT FEATURES

- Intended for Cleanrooms, Hospitals, Hi-Tech Manufacturing, Laboratory, Food Processing Facilities, Commercial Kitchens, and more
- · Recessed mount installation
- · Red or green legend
- Fixture is certified to UL standards by Intertek Testing Laboratory. IP65 rated per IEC60598. Meets ISO4/Class 1 Cleanroom Standards
- This product was Made in America and complies with the Buy American Act requirements



ESCR Series

c Usus Us









ORDERING INFORMATION

Example: ESCR-HC/IC-SF-LED-UN-RW

ECS	R			SF	LED
Series	Mounting R = Surface	Housing HC =20Ga. CRS Painted HS = 20Ga. Stainless Steel	Overlap Frame OC = 20Ga. CRS Painted OS = 20Ga. SS Brushed	Face SF = Single Face	Lamp Type LED = LED Module

Voltage	Lettering	Options
12 = 120V	RW = Red Letters	EM = Emergency Battery
27 = 277V	GW = Green Letters	
UN = Universal (120V-277V)		*If stored, batteries should be fully recharged
		every six months and kept between 0°C-25°C
		to maintain optimal battery capacity.

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

CLEANROOM EXIT RECESSED SERIES



SPECIFICATIONS

CONSTRUCTION: 20-Gauge formed cold rolled steel or brushed stainless steel housing with continuous seam welds.

FRAME: Single face overlapping doorframe in 18-gauge cold rolled steel or 18-gauge brushed stainless steel.

LENS: .125 clear polycarbonate lens.

ELECTRICAL: Long life LED system illuminates Red or Green legend. Optional single face or double face. 7W.

LEGEND: Legend illuminated by internal high output LEDs. Lettering 6" high with .750" stroke. Polycarbonate red or green filter panel. Field selectable chevron inserts.

FINISH: White antimicrobial powder coat finish following multi-stage iron phosphate pre-treatment. Stainless steel housing and overlapping frame will be left unpainted if specified.


GASKET: Closed cell EPDM and closed cell silicone gaskets prevent air contaminations from entering the fixture.


INSTALLATION: Recessed installation.

WARRANTY: Limited five (5) year warranty.

FASTENERS: Stainless steel Phillips flathead fasteners with captive cage nuts. Finish to match doorframe.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory. IP65 rated per IEC60598. Meets ISO4/Class 1 Cleanroom Standards. This product is Made in America and complies with the Buy American Act (BAA).





DIMENSIONAL DATA



Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.