

# HNL STEP LIGHT SERIES

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 PRODUCT: \_\_\_\_\_  
 APPROVED BY: \_\_\_\_\_

## PRODUCT FEATURES

- Intended for Fall Prevention in healthcare settings, including Patient Rooms, Patient Bathrooms, Corridors, Lobbies, Waiting Rooms, Nurses' Stations, and more
- Four faceplate options: horizontal or vertical hood, louver, and open frame
- Constructed of durable die-cast aluminum with integral embedded driver (3W)
- Available in White CCTs: 3000K, 4000K, 5000K and Amber LED
- Optional photocell or occupancy sensor with select faceplates



HNL

## ORDERING INFORMATION

Example: HNL-HH-30-UN-NF-AM



HNL			UN		
<b>Series</b>	<b>Faceplate</b> HH = Horizontal Hood HL = Horizontal Louver OF = Open Frame* VH = Vertical Hood  *Can be installed horizontally or vertically.	<b>Color Temp.</b> 30 = 3000K 40 = 4000K 50 = 5000K LA = Amber LED	<b>Voltage</b> UN = Universal (120V-277V)	<b>Options</b> NF = None PC = Photocell* OC = Occupancy Sensor**  *Can only be used with HH Faceplate. PC & OC cannot be used together. **OC N/A with Amber. Can only be used with HH Faceplate. PC & OC cannot be used together.	<b>Finish</b> AM = Antimicrobial White CC = Custom Color*  *Must specify RAL number at time of order and if a antimicrobial finish is needed. Subject to set-up fees.

## SPECIFICATIONS

**HOUSING:** Durable die-cast aluminum material. Available with four different faceplates: Horizontal Hood, Horizontal Louver, Open Frame (can be installed vertically or horizontally), and Vertical Hood.

**LED:** Available in three color temperatures 3000K, 4000K, and 5000K with maximum 3-step MacAdam variation allowance. Amber LED is also available. Minimum 50,000 hours with 70% lumen maintenance in an ambient environment 25°C temperature, compliant with IES LM-80 testing data.

**ELECTRICAL:** Integrated embedded driver (3W). Standard 0-10V Dimming with 10-100% range.

**FINISH:** White antimicrobial finish powder coat finish following multi-stage iron phosphate pretreatment on all exposed room-side surfaces, unless otherwise specified. Custom color available, must specify RAL number and indicate if antimicrobial finish is needed (set-up fees may apply).


**INSTALLATION:** Recessed installation. J-Box and hardware by others.

**WARRANTY:** 5 Year Warranty.


**LABEL:** Fixture is certified to UL standards for Wet Location rating (under covered ceiling).

## DIMENSIONAL DATA


**HORIZONTAL HOOD WITH PH/OC**




**HORIZONTAL HOOD WITHOUT PH/OC**




**VERTICAL HOOD**



**OPEN FRAME (VERTICAL OR HORIZONTAL)**



**VERTICAL LOUVER**



## PERFORMANCE DATA\*

\*Data is with 80 CRI chip. LEDs are frequently updated therefore values may change without notice.

MODEL	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
HNL-OF	3000K	250	66	3.8
	4000K	240	63	3.8
	5000K	253	67	3.8
	Amber LED	170	45	3.8
HNL-VH	3000K	92	24	3.8
	4000K	82	22	3.8
	5000K	95	25	3.8
	Amber LED	61	16	3.8
HNL-HH	3000K	130	34	3.8
	4000K	120	32	3.8
	5000K	133	35	3.8
	Amber LED	88	23	3.8
HNL-HL	3000K	124	33	3.8
	4000K	114	30	3.8
	5000K	127	33	3.8
	Amber LED	85	22	3.8

