

PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____

PRODUCT FEATURES

- Intended for Public Areas, MRI Rooms, Corridors, Stairways, Underpasses, Parking Garages, Restrooms, Lobbies, Schools, and more.
- Surface Wall Mount Installation
- This product was Made in America and complies with the Buy American Act requirements



LAM

ORDERING INFORMATION

Example: LAM1-AL-L2401-LC3-UN-BK



LAM					IC
Series	Size* 1 = 1ft (14.88") 2 = 2ft (26.98") 4 = 4ft. (50.10") *Dimensional data on page 2.	Frame AL = Aluminum Painted SS = Stainless Steel Brushed SSP = Stainless Steel Painted CR = Cold Rolled Steel Painted* CF = Custom Frame *Not recommended for outdoor applications.	Lumen Output* L1 = Standard** L2 = Medium L3 = High*** L3 = Max**** *Subject to change. **N/A with LAM1. N/A with OC Sensor. ***N/A with OC sensor. ****Only available in LAM4.	Lamp Type 30 = 3000K 35 = 3500K 40 = 4000K 50 = 5000K	Circuit IC = 1 Circuit

LC3			
Lens LC3 = .125 White Frosted Poly.	Voltage 12 = 120V 27 = 277V 34 = 347V UN = Universal (120V-277V)	Finish* Blank = SS Brushed is specified BK = Black WH = Matte White BZ = Bronze CC = Custom Color** *Outdoor rated finish standard unless otherwise specified. Leave blank for SS Brushed. Must specify if antimic. finish is required. **Subject to additional fees. Must specify RAL number at time of PO.	Options FZ1 = Fuse (120V) FZ2 = Fuse (277V) PC = Photocell (must use with Surface Adapter)* SA = Surface Adapter (not ADA compliant) OC = Occupancy Sensor** EM1 = Emerg. Bat. (must use with Surface Adapter)** AH = Allen Head screws with center pin reject CUS = Custom band option, consult factory PM = Pendant Mount RM = Tandem Mount *Must specify voltage. **Cannott use EM1 & OC together for LAM1. Remote battery for LAM1.

SPECIFICATIONS

HOUSING: Die-formed, seam welded and ground smooth marine grade aluminum (standard).

FRAME: Die-formed, seam welded and ground smooth frame available in aluminum (standard), stainless steel and cold rolled steel. Custom band options available, consult factory.

LENS: .125 White UV-stabilized polycarbonate lens for maximum diffusion.

LED: Available in three color temperatures 3500K, 4000K and 5000K with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory.

ELECTRICAL: 0-10V Dimming available with 1-100% range.

REFLECTOR: Die-formed aluminum. Removable for easy installation and maintenance.

FASTENERS: Tamper-resistant Torx® head fasteners with center pin reject.

FINISH: Black, white or bronze textured powder coat paint or optional custom color following multistage iron phosphate pretreatment.

GASKET: Black neoprene gasket around interior door frame to prevent water and dust infiltration.

WARRANTY: New Star Promise.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratories for Wet Locations. ADA Compliant.






The Lampa Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal Resistant architectural luminaires when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse.*

*Exclusions to the New Star Promise are gunfire and chemical reactions

DIMENSIONAL DATA



PERFORMANCE DATA

MODEL	OUTPUT	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
LAM1	L2 = Medium	4000K	650	58	12.5
	L3 = High	4000K	975	58	18.75
LAM2	L1 = Low	4000K	650	58	12.5
	L2 = Medium	4000K	1300	58	25
	L3 = High	4000K	1950	58	37.5
LAM4	L1 = Low	4000K	1300	58	25
	L2 = Medium	4000K	2600	58	50
	L3 = High	4000K	3900	58	75
	L4 = Max	4000K	5800	58	100