

NSELC CHICAGO-APPROVED EXIT/STAIR EDGELIT SERIES



PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____

PRODUCT FEATURES

- Chicago-Approved edgelit sign for stairwells, corridors, commercial settings, and more
- Ceiling or wall surface mount installation
- Red legend, optional single or double face
- Fixture is certified to UL standards for Damp Locations (0°C - 50°C)
- This product is Assembled in America and complies with Buy American Act requirements



NSELC Series

ORDERING INFORMATION

Example: NSELC-SF-RW-AL-DA



NSELC		RW			
Series	Face SF = Single Face DF = Double Face	Lettering RW = Red Letters	Housing AL = Aluminum WH = White	Battery (blank) = AC Only EM-WC = Battery Backup (cold weather std.)	Directional Arrows NA = Exit No Arrow SNA = Stair No Arrow DA = Exit Double Arrow SDA = Stair Double Arrow RA = Exit Right Arrow* SRA = Stair Right Arrow* LA = Stair Left Arrow* SLA = Stair Left Arrow* LARA = Exit Left/Right Arrow** SLARA = Stair Left/Right Arrow** *Available in single face configuration only. **Available in double face configuration only.



New Star Lighting

2225 W Pershing Rd, Chicago, IL 60609
 (773) 847-1400
 www.newstarlighting.com

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

NSELC CHICAGO-APPROVED EXIT/STAIR EDGELIT SERIES

SPECIFICATIONS

HOUSING: Premium-grade, extruded aluminum housing (also available in optional white powder-coated finish). Single or double face configurations.

LENS: UV-stabilized silk screened acrylic edgelit panel provides consistent, uniform illumination.

ELECTRICAL: Dual 120/277 voltage, 50/60Hz standard. Energy-efficient, long life Red LEDs. Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing. 4.8V long life, maintenance-free rechargeable NiCd battery (EM models only). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

FASTENERS: Stainless steel Philips fasteners.

INSTALLATION: Diecast aluminum mounting canopy provided for universal top, end or back mount.

WARRANTY: Five (5) year warranty on all electronics and housing. Battery prorated for five years.

LABEL: Fixture UL Listed for Damp Locations (0°C - 50°C). This product meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. Meets city of Chicago requirements. Certified to CEC under Title 20 Regulations. This product is Assembled in America and complies with the Buy American Act (BAA).

DIMENSIONAL DATA

