

PROJECT: \_\_\_\_\_  
 TYPE: \_\_\_\_\_  
 PRODUCT: \_\_\_\_\_  
 APPROVED BY: \_\_\_\_\_



NSELN Series

## PRODUCT FEATURES

- NYC-Compliant edgelit sign for stairwells, corridors, commercial settings, and more
- Ceiling or wall surface mount installation
- 8" EXIT red letters, optional single or double face
- Fixture is certified to UL standards for Damp Locations (0°C - 50°C)
- This product is Assembled in America and complies with Buy American Act requirements

## ORDERING INFORMATION

Example: NSELN-SF-RW-C-WH-SDT



NSELN		RW				
<b>Series</b>	<b>Face</b> SF = Single Face DF = Double Face	<b>Lettering</b> RW = Red Letters	<b>Panel</b> C = Clear* M = Mirror WH = White  *With single face only	<b>Housing Color</b> WH = White BK = Black AL = Aluminum	<b>Battery</b> (blank) = AC Only EM = Battery Backup	<b>Options</b> SDT = Self-Diagnostics* SPV = 208/220/240 Volt, 50/60Hz**  *Available only with EM units **Not available with SDT



**New Star Lighting**

2225 W Pershing Rd, Chicago, IL 60609  
 (773) 847-1400  
[www.newstarlighting.com](http://www.newstarlighting.com)

Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

© 2025, New Star Lighting. All rights reserved. Unauthorized duplication or distribution is prohibited.

## SPECIFICATIONS

**CONSTRUCTION:** Premium-grade, extruded aluminum housing (also available in optional black or white powder-coated finish). Single or double face configurations. Self-adhesive Chevron appliques and guide template provided for directional indication.

**LENS:** UV-stabilized clear acrylic edgelit panel provides consistent, uniform illumination. Double face utilizes factory-installed silver or white mylar background panel. New York City compliant 8" EXIT letters.

**ELECTRICAL:** Dual 120/277 voltage standard, 208/220/240 Volt 50/60Hz optional. Energy-efficient, long life Red LEDs. Charge rate/power "ON" LED indicator light and push to test switch for mandated code compliance testing. 4.8V long life, maintenance-free rechargeable NiCd battery (EM models only). Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination. Fully automatic solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours.

**FASTENERS:** Stainless steel Philips fasteners.

**INSTALLATION:** Aluminum mounting canopy included for top, end or back mount. Available in optional black or white powder-coated finishes.

**WARRANTY:** Five (5) year warranty on all electronics and housing. Battery prorated for five years.

**LABEL:** Fixture UL Listed for Damp Locations (0°C - 50°C). This product meets NFPA 101 Life Safety Code, NEC, OSHA, Local and State Codes. This product is Assembled in America and complies with the Buy American Act (BAA).

## DIMENSIONAL DATA

