STAIRWELL SERIES: QUICK SHIP



| PROJECT: |
|--------------|
| TYPE: |
| PRODUCT: |
| APPROVED BY: |

PRODUCT FEATURES

- Intended for Corridors, Stairways, Restrooms, Lobbies, Schools, and more
- 5 Day Quick Ship for orders under 50 fixtures. Consult factory for large quantities or additional fixture options
- · Surface mount linear fixture available in 2ft
- · Cold rolled steel low-profile housing
- Frosted polycarbonate lens for even light distribution
- This product is Made in America and complies with the Buy American Act requirements















ORDERING INFORMATION

Example: STWL2-T-L227-UN-QS

| STWL | 2 | Т | | |
|--------|---|-------|---|-------------------------------|
| Series | Nominal Size 2 = 2ft | Style | Lumen Output* L2 = Standard | Color Temp. 27 = 2700K |
| | *Nominal size. Dimensional Data on Page 2. | | *Subject to change. Performance Data on Page 3. | 35 = 3500K |

| UN | | QS |
|---------------------------------------|----------------------------------|-------------------------------------|
| Voltage UN = Universal (120V-277V) | Options PH = Phillips Head Screw | Quick Ship QS = Quick Ship |
| | | *Required for Emergency Battery. |

STAIRWELL SERIES: QUICK SHIP



SPECIFICATIONS

CONSTRUCTION: 22-Gauge cold rolled steel internally reinforced housing.

LENS: .10" Linear prismatic frosted UV-stabilized polycarbonate lens for even light distribution.

LED: Available in select color temperatures: 2700K and 3500K with maximum 3-step MacAdam variation allowance. Minimum 80 CRI standard.

ELECTRICAL: 0-10V dimming standard.

REFLECTOR: 22-Gauge cold rolled steel in high reflective white finish.

FASTENERS: Tamper resistant Torx® head screws with center pin reject. Optional Phillips screws available. Raw unpainted fastener finish.

FINISH: White powder coat finish following multistage iron phosphate pretreatment.


INSTALLATION: Surface wall mount installation. J-Box and hardware by others.


WARRANTY: New Star Promise.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory for Damp Locations.

DIMENSIONAL DATA









The StairWell Quick Ship Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaries when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse*.

*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.



Specifications and dimensions are subject to change without notice. For additional options and dimensional details, please consult your New Star Lighting representative.

08212024

STAIRWELL SERIES: QUICK SHIP



PERFORMANCE DATA

*LEDs are frequently updated therefore values may change without notice.

| MODEL | ОИТРИТ | COLOR TEMP. | LUMENS DELIVERED | EFFICACY (Im/W) | INPUT POWER (W) |
|-------|--------------|-------------|------------------|-----------------|-----------------|
| STWL2 | L2 =Standard | 4000K | 1500 | 100 | 15 |