STAIRWELL SERIES: QUICK SHIP



| PROJECT: |
|--------------|
| TYPE: |
| PRODUCT: |
| APPROVED BY: |

PRODUCT FEATURES

- Intended for Corridors, Stairways, Restrooms, Lobbies, Schools, and more
- 5 Day Quick Ship for orders under 50 fixtures. Consult factory for large quantities or additional fixture options
- · Surface mount linear fixture available in 2ft
- · Cold rolled steel low-profile housing
- Frosted polycarbonate lens for even light distribution
- This product is Made in America and complies with the Buy American Act requirements













ORDERING INFORMATION

Example: STWL2-T-L227-UN-QS

| STWL | 2 | Т | | |
|--------|---|-------|--|---|
| Series | Nominal Size 2 = 2ft *Nominal size. Dimensional Data on Page 2. | Style | Lumen Output* L2 = Standard *Subject to change. Performance Data on Page 3. | Color Temp. 27 = 2700K 35 = 3500K |

| <u> </u> | | |
|-----------------------------------|--------------------------|-------------------------|
| UN | | QS |
| Voltage | Options | Quick Ship |
| UN = Universal (120V-277V) | PH = Phillips Head Screw | QS = Quick Ship |
| | | |
| | | |
| | | *Required for Emergency |
| | | Battery. |
| | | |
| | | |

STAIRWELL SERIES: QUICK SHIP



SPECIFICATIONS

CONSTRUCTION: 22-Gauge cold rolled steel internally reinforced housing.

LENS: .10" Linear prismatic frosted UV-stabilized polycarbonate lens for even light distribution.

LED: Available in select color temperatures: 2700K and 3500K with maximum 3-step MacAdam variation allowance. Minimum 80 CRI standard.

ELECTRICAL: 0-10V dimming standard.

REFLECTOR: 22-Gauge cold rolled steel in high reflective white finish.

FASTENERS: Tamper resistant Torx® head screws with center pin reject. Optional Phillips screws available. Raw unpainted fastener finish.

FINISH: White powder coat finish following multistage iron phosphate pretreatment.


INSTALLATION: Surface wall mount installation. J-Box and hardware by others.


WARRANTY: New Star Promise.

LABEL: Fixture is certified to UL standards by Intertek Testing Laboratory for Damp Locations.

DIMENSIONAL DATA









The StairWell Quick ShipSeries is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal Resistant achirtectural luminares when installed according to our instructions for the life of the original installation if the fixture should faile due to physical abuse.*

*Exclusions to the New Star Promise are gunfire and chemical reactions



STAIRWELL SERIES: QUICK SHIP



PERFORMANCE DATA

*LEDs are frequently updated therefore values may change without notice.

| MODEL | ОИТРИТ | COLOR TEMP. | LUMENS DELIVERED | EFFICACY (Im/W) | INPUT POWER (W) |
|-------|--------------|-------------|------------------|-----------------|-----------------|
| STWL2 | L2 =Standard | 4000K | 1500 | 100 | 15 |