


PROJECT: _____
 TYPE: _____
 PRODUCT: _____
 APPROVED BY: _____

PRODUCT FEATURES

- Intended for Minimum to Maximum Correctional Facilities, Detention Centers, and more
- Two-aperture wall mount clamshell design with contraband drop slot between ceiling and back of luminaire available in 2ft and 4ft
- Inner and outer lens secured by “Z” bracket retention system with 6” stud spacing for maximum strength
- This product is Made in America and complies with the Buy American Act requirements



SUD

ORDERING INFORMATION

Example: SUD2-B-LA401C-A/C-UN



SUD					
Series	Size* 2 = 2ft 4 = 4ft *Nominal Size. Dimensional Data on Page 2.	Gauge B = 14Ga. CRS Painted C = 16Ga. CRS Painted D = 18Ga. CRS Painted E = 14Ga. SS Brushed F = 16Ga. SS Brushed G = 18Ga. SS Brushed H = 14Ga. SS Painted J = 16Ga. SS Painted K = 18Ga. SS Painted	Lumen Output LA = 1 Up/1 Down LB = 1 Up/2 Down LC = 2 Up/2 Down LD = 2 Up/1 Down LE = 0 Up/1 Down LF = 1 Up/0 Down *Performance Data on Page 3.	Color Temp. 35 = 3500K 40 = 4000K 50 = 5000K	Circuits 1C = 1 Circuit 2C = 2 Circuits* *Select 2C for Up/Down compartments to be independently circuited/controlled

Outer Lens 0 = No Lens A = .125 Clear Poly. B = .156 Clear Poly. 1 = .187 Clear Poly. 2 = .250 Clear Poly. 3 = .375 Clear Poly. 5 = .187 Clear Temp. Glass 6 = .250 Clear Temp. Glass 7 = .375 Clear Temp. Glass* 8 = .500 Clear Temp. Glass* 9 = .750 Clear Temp. Glass* *Must use with 14Ga.	Inner Lens A = .125 Prismatic Acrylic B = .125 Prismatic Poly. C = .156 Prismatic Poly. D = .187 Prismatic Poly. F = .156 Prismatic Acrylic G = .140 DR Acrylic LC3 = .125 White Frosted Poly.	Voltage 12 = 120V 27 = 277V 34 = 347V UN = Universal (120V - 277V)	Options FZ1 = Fuse (120V) FZ2 = Fuse (277V) LN = LED Night Light* EL1 = Emerg. Bat. LED Low (1100-1250 lm)** EL2 = Emerg. Bat. LED High (1900-2000 lm)** AH = Allen Head screws with center pin reject SL = Flush Botton Switch on Left (120V) SR = Flush Button Switch on Right (120V) AM = Antimicrobial finish on exposed surfaces CEL1 = CA Title 24 Emerg. Batt LED*** *3500K non-dimming Night Light with integrated switch allows light levels at 100%, 70%,40% and 10%. Located in “Down” compartment. **Illuminates “Down” compartment with integral test switch. If stored, batteries should be fully recharged every six months and kept between 0°C-25°C to maintain optimal battery capacity. ***Consult factory for options. Depending on options specified. Battery may need to be remote.
---	--	---	---

SPECIFICATIONS

HOUSING: Die-formed, seam welded, and ground smooth two-aperture wall mount clamshell design in cold rolled steel or stainless steel clamshell design. Incorporates a removable reflector unitized with all electrical components for easy installation and maintenance. Rounded housing shape designed to withstand physical abuse.

BACKPLATE: Die formed with contraband drop slot and embossed mounting holes (material to match housing). Security caulking between ceiling and fixture is not required with this backplate design.

GAUGE: 16-Gauge full length continuous, staked piano hinge with welded ends to prevent removal (material to match housing).

LENS: Outer and Inner lens options secured by "Z" retainers with welded studs spaced six inches apart for maximum strength.

LED: Available in three color temperatures 3500K, 4000K and 5000K with maximum 3-step MacAdam variation allowance. Other color temperatures available, consult factory. Minimum 80 CRI standard. 0-10V dimming available with 10-100% range and 1-100% range. Must specify dimming under options.

ELECTRICAL: 120-277VAC or 347VAC, 50/60HZ electrical input high power factor electronic, constant current driver (<20% THD, >0.95 PF). Standard 0-10V Dimming with 1-100% range.

FASTENERS: Tamper-resistant Torx® head fasteners.

FINISH: White powder coat finish following multi-stage iron phosphate pre-treatment. Optional antimicrobial finish.

INSTALLATION: Surface wall installation.

WARRANTY: New Star Promise.

LABEL: Fixture is certified for Wet Locations (under covered ceilings) to UL standards by Intertek Testing Laboratories. This product is Made in America and complies with the Buy American Act (BAA).






The SUD Series is covered by our New Star Promise.

Our promise means we will repair or replace any of our High Abuse or Vandal-Resistant architectural luminaires when installed according to our instructions for the life of the original installation if the fixture should fail due to physical abuse*.

*Damage caused by gunfire and chemical reactions is not covered by the New Star Promise.

DIMENSIONAL DATA

Fixture weight varies and is dependent upon chosen specifications. Average weight of the SUD2 is 30lb. Average weight of the SUD4 is 45lb. Consult factory for additional information.



PERFORMANCE DATA

*Data is with 80 CRI chip at 4000K. LEDs are frequently updated therefore values may change without notice.

MODEL	OUTPUT	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
SUD2	LA = 1 Up/1 Down	4000K	2750	110	25
	LB = 1 Up/2 Down	4000K	4125	110	37.5
	LC = 2 Up/2 Down	4000K	5500	110	50
	LD = 2 Up/1 Down	4000K	4125	110	37.5
	LE = 0 Up/1 Down	4000K	1375	110	12.5
	LF = 1 Up/0 Down	4000K	1375	110	12.5
SUD4	LA = 1 Up/1 Down	4000K	5500	110	50
	LB = 1 Up/2 Down	4000K	8250	110	75
	LC = 2 Up/2 Down	4000K	11000	110	100
	LD = 2 Up/1 Down	4000K	8250	110	75
	LE = 0 Up/1 Down	4000K	2750	110	25
	LF = 1 Up/0 Down	4000K	2750	110	25

