

## STAIRWELL TRES SERIES: QUICK SHIP

STWL2-T

### FEATURES:

- Intended for Corridors, Stairways, Restrooms, Lobbies, Schools, and more
- 5 Day Quick Ship for orders under 50 fixtures. Consult factory for large quantities or additional fixture options
- Surface mount linear fixture available in 2ft
- Cold rolled steel low-profile housing
- Frosted polycarbonate lens for even light distribution
- This product complies with the Buy American Act requirements



### RELATED PRODUCTS:

- [Stairwell \(STWL\) Full Range of Ordering Options](#)
- [Victory Narrow \(VICN\)](#)

SWTL2



### SPECIFICATIONS

**CONSTRUCTION:** 22 gauge cold rolled steel internally reinforced housing.

**LENS:** .10 linear prismatic frosted polycarbonate lens for even light distribution.

**LED:** Available in select color temperatures: 2700°K and 3500°K with maximum 3-step MacAdam variation allowance. Minimum 80 CRI standard.

**FASTENERS:** Stainless steel Phillips flat head screws. Raw unpainted screw finish.

**ELECTRICAL:** 0-10V dimming standard.

**REFLECTOR:** 22 gauge cold rolled steel in high reflective white finish.

**FINISH:** White powder coat finish following multistage iron phosphate pretreatment.

**INSTALLATION:** Surface wall mount installation. JBox and hardware by others.

**WARRANTY:** Limited five (5) year warranty.

**LABEL:** Fixture is certified to UL standards by Intertek Testing Laboratory for Damp Location.

## STAIRWELL TRES SERIES: QUICK SHIP

### STWL2-T

#### ORDERING INFORMATION

EXAMPLE: STWL2-T-L235-UN-QS

SERIES	SIZE*	STYLE	LUMEN OUTPUT*	COLOR TEMP.	VOLTAGE	OPTIONS	
STWL	2	T	L2		UN		QS
	2 = 2ft		L2 = Standard	27 = 2700°K 35 = 3500°K	UN = Universal (120V-277V)	TH = Torx Head Screws with center pin	QS = Quick Ship

\*Nominal  
Size.

\*Subject to change.

#### PERFORMANCE DATA\*

\*Data is with 80 CRI chip. LEDs are frequently updated therefore values may change without notice.

MODEL	OUTPUT	COLOR TEMP.	LUMENS DELIVERED	EFFICACY (lm/W)	INPUT POWER (W)
STWL2	L2 = Standard	4000°K	1500	100	15

#### DIMENSIONAL DATA

Fixture weight varies and is dependent upon chosen specifications. Consult factory for additional information.

